

Conical sheet steel lighting poles

Hot galvanized steel as per UNI EN ISO 1461:
Standard processes to the pole pag. 6



article	L mm	l mm	s mm	D mm	d mm	m ²	door article	weight kg	qty pack
4360	3.500	500	3	95	60	0,85	4300/LDT	20,00	1
4400	4.000	500	3	100	60	1,00	4300/LDT	24,00	1
4460	4.500	500	3	105	60	1,17	4300/LDT	28,00	1
4500	5.000	500	3	110	60	1,34	4300/LDT	32,00	1
4560	5.500	500	3	115	60	1,51	4300/LDT	37,00	1
4560/4	5.500	500	4	115	60	1,51	4300/LDT	48,00	1
4600	6.000	500	3	120	60	1,70	4300/LDT	41,00	1
4680	6.800	800	3	128	60	2,01	4301/LDT	48,00	1
4680/4	6.800	800	4	128	60	2,01	4301/LDT	64,00	1
4780	7.800	800	3	138	60	2,43	4301/LDT	59,00	1
4780/4	7.800	800	4	138	60	2,43	4301/LDT	77,00	1
4880	8.800	800	3	148	60	2,88	4301/LDT	70,00	1
4880/4	8.800	800	4	148	60	2,88	4301/LDT	92,00	1
4930	9.300	800	3	153	60	3,11	4301/LDT	76,00	1
4930/4	9.300	800	4	153	60	3,11	4301/LDT	100,00	1
4980	9.800	800	3	158	60	3,36	4301/LDT	82,00	1
4980/4	9.800	800	4	158	60	3,36	4301/LDT	108,00	1
41030	10.300	800	3	163	60	3,61	4301/LDT	88,00	1
41030/4	10.300	800	4	163	60	3,61	4301/LDT	117,00	1
41080	10.800	800	3	168	60	3,87	4301/LDT	94,50	1
41080/4	10.800	800	4	168	60	3,87	4301/LDT	125,00	1
41130	11.300	800	3	173	60	4,14	4301/LDT	102,00	1
41130/4	11.300	800	4	173	60	4,14	4301/LDT	133,00	1
41180/4	11.800	800	4	178	60	4,41	4301/3	143,00	1
41230/4	12.300	800	4	183	60	4,69	4301/3	152,00	1
41280/4	12.800	800	4	188	60	4,99	4301/3	162,00	1